



www.bisonpumps.com

BISON PUMPS
98 BANGOR STREET
PO BOX 977
HOULTON, ME 04730
1-800-339-2601
INFO@BISONPUMPS.COM


TAMPER PROOF CAP AND HARDWARE INSTALLATION INSTRUCTIONS

The purpose of the tamper proof kit is to remove the handle and install cap to deter unauthorized use of your Bison Hand Pump.

This tamper proof kit includes the following items:

- (1) Tamper proof cap
- (1) 3/8" x 1 1/2" clevis pin and hair cotter pin (top of handle)
- (1) 3/8" x 2" clevis pin and hair cotter pin (links to body)
- (2) compression springs (one on each of the connections)
- (2) 3/8" flat washers (one on each of the connections)

1. Remove the shoulder bolt that goes through the top of the handle and the eyelet.
2. Remove the 3/8" x 2" bolt fastened in the bottom of the links attached to the body of the pump.
3. Remove the handle.
4. Using a 3/8" drill bit, drill out the holes at the top of the handle (one of the holes is currently 5/16". They both need to be 3/8" to accommodate the new hardware).



To re-install the handle after cap is removed:

1. Compression spring on the clevis pin
2. Slide through the handle (or links)
3. Flat washer on the outside
4. Then hair cotter pin.

If you have any questions, please call 1-800-339-2601.